

APPROVAL SHEET

CUSTOMER-- : _____

DESCRIPTION: S-480-24

CUSTOMER PART NO: _____

OUR MODEL NO: 24V20A

DATE: 2021-03-12

确认签字，盖章后请返回承认书一份

PLEASE RETURN TO US ONE COPY OF “SPECIFICATION FOR APPROVAL” WITH YOUR APPROVED SIGNATURES

DATE: _____		
APPROVAL	CHECK	ENGINEER

CUSTORMER:		
DATE: _____		
APPROVAL	CHECK	ENGINEER

Switching Power Supply Specifications

Table of contents

1. 描述: DESCRIPGION.....	2
2. 输入特性: INPUT CHARACTERISTICS.....	2
3. 输出特性: OUTPUT CHARACTERISTICS.....	2-3
4. 保护功能: PROTECTION REQUIREMENT.....	3
5. 环境条件: ENVIRONMENTAL REQUIREMENT.....	3
6. 安规要求: SAFETY REQUIREMENT.....	3
7. 外形尺寸: OUTLINE DIMENSION	4

1. 描述 (GENERAL DESCRIPTION):

本规格书适应于 S-480-24型号的开关电源。

This specification defines the input, output, performance characteristics, environment, noise and safety requirements for the S-480-24 switching type power adapter.

2. 输入特性 (INPUT CHARACTERISTICS):

2.1 额定电压 (Nominal voltage) : 100-120/200-240VAC

2.2 输入频率 (Input Frequency) :

额定频率 (Nominal Frequency) :50/60HZ

频率范围 (Variation Frequency) :47-63Hz

2.3 输入电流 (Input Current) : 7.8A(110VAC)/3.85A(220VAC)

2.4 浪涌电流(Inrush Current): 3000Amax at 25°C, 230VAC

2.5 漏电流(Leakage Current): <3.5mA

3 输出特性 (OUTPUT CHARACTERISTICS) :

3.1 额定电压 (Nominal voltage) :24VDC+/-1%

3.2 线性调整(Line Regulation):0.5%

3.3 负载调整(Load Regulation) :2%

3.4 额定电流(Nominal current):20A

3.5 波纹和噪音(Ripple And Noise):

<300mV(220VAC,20Mhz, terminated with a 0.1uF & 47uF parallel capacitor at the output connector)

<300mV(在220VAC 输入条件下, 采用20MHz 带宽, 并在输出连接器端口并联0.1uF 和47uF 两个电容测量)

3.6 启动时间(Setup time):

<1s(220VAC,Max.Load) / <1ms(110VAC,Max.Load)

<1s ms(220VAC 输入, 最大负载) / <1s ms(110VAC 输入, 最大负载)

3.7 上升时间(Rise Time):

<10ms(220VAC,Max.Load) / <10ms(110VAC,Max.Load)

<10ms(220VAC 输入, 最大负载) / <10ms(110VAC 输入, 最大负载)

3.8 保持时间(Hold up Time):

<1ms(220VAC,Max.Load) / <1ms(110VAC,Max.Load)

<1ms(220VAC 输入, 最大负载) / <1ms(110VAC 输入, 最大负载)

3.9 效率(Efficiency):

81.8%(110VAC,Max.Load)

81.8%(110VAC 输入, 最大负载)

86.2%(220VAC,Max.Load)

86.2%(220VAC 输入, 最大负载)

4. 输出保护功能(OUTPUT PROTECTION REQUIREMENT):

4.1 短路保护功能(Short Circuit Protection):

该电源在短路解除时,能自动恢复.

The power supply will be recovered when short circuit faults removed.

4.2 过流保护(Over current protection):

负载电流大于23.5A(110Vac)或者23.5A(220Vac)时进入锁存模式, 空载时电源恢复.

The power supply will be recovery from latch mode when load current removed.

5. 环境条件(ENVIRONMENTAL REQUIREMET):

5.1 工作温度(Operating Temperature): -10°C-25°C (满载/Max. Load)

5.2 储藏温度(Storage Temperature): -20°C to 85°C.

5.3 工作湿度(Relative Humidity): 5%(0°C)~95%(45°C)

5.4 振动(Vibration): 10-500Hz, 2g, 10min

5.5 MTFB: 2years

6. 安规要求(SAFETY REQUIREMENT)

6.1 安规标准(Safety standards): EN60950

6.2 耐压(Withstand voltage):

输入对输出: 1.5KVAC 1分钟

I/P-O/P:1.5KVAC 1minute

输入对地: 1.5KVAC 1分钟

I/P-FG:1.5KVAC 1minute

输出对地: 0.5KVAC 1分钟

O/P-FG:0.5KVAC 1minute

7.外形尺寸 (OUTLINE DIMENSION):

L*W*H=240*125*65mm Weight=1352g

