

Features:

- Simple, compact and generous machine appearance
- Super wide mains input range
- Excellent microprocessor to ensure reliable operation
- Automatic adjustment of the AC mains power boost, step-down, stable voltage output
- Mains restart function
- Output modified sine wave
- Automatic charge in off-mode
- Cold start function
- Compatible generators



Line Interactive UPS		
Model	XF-2000	GTXF 2000
Capacity	2000VA /1200W	
Input		
Voltage	220VAC	
AC Mains Input Voltage Range	145-280 VAC (same as AC mains)	
Frequency	50 Hz	
Output		
Voltage Range(Battery Mode)	±10%	
Frequency Range(Battery Mode)	50 Hz ±1 Hz	
Transfer Time	<6ms	
Waveform(Battery)	Modified sine wave	
Battery		
Battery Type & Quantity	12V 12Ah x 2	
Battery Charging Time	6 hours charge to 90%	
LED Indicators		
AC Mode	Green light	
Battery Mode	Red light flash	
Audible Alarm		
Battery Mode	Alarm beeps every six seconds	
Low Battery	Alarm beeps every second	
Overload	Alarm beeps twice every second	
Fault	Alarm beeps continuously	
Protection Function		
Comprehensive Protection	Overload, deep discharge and over-charge protection	
Environment		
Temperature And Humidity	Relative humidity 0-90% and temperature 0- 40°C (No-condensing)	
Noise	less than 40dB at one meter distance	
Physical Function		
Dimensions D X W X H (mm)	405*144*213	
Net Weight (kgs)	17	